

## 22" Full HD monitor with VA panel and a height adjustable stand

The ProLite XUB2294HSU featuring VA panel technology guarantees accurate and consistent colour reproduction with wide viewing angles. Input configuration including HDMI, DisplayPort and a USB hub assure compatibility with many platforms. The 150mm ergonomic height adjustable stand with pivot function allows you to easily adjust the monitor position to your preferences making it a solid solution for both home and the office.

### VA

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

### HAS (150mm) + Pivot (rotation both sides)

With a height adjustable stand you will create an ergonomic work posture and position that meets all health and safety requirements. This will not only prevent any health issues but will also increase your productivity. The pivot function allows the screen to rotate from landscape to portrait orientation. This functionality can be useful if the application requires more height than width.

## 01 DISPLAY CHARACTERISTICS

|                      |   |
|----------------------|---|
| Design               | 3-side borderless   |
| Diagonal             | 21.5", 54.5cm   |
| Panel                | VA, matte finish  |
| Native resolution    | 1920 x 1080 @75Hz (2.1 megapixel Full HD)                             |
| Aspect ratio         | 16:9  |
| Panel brightness     | 250 cd/m <sup>2</sup>   |
| Static contrast      | 3000:1  |
| Advanced contrast    | 80M:1   |
| Response time (MPRT) | 1ms   |
| Viewing zone         | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support       | 16.7mIn (sRGB: 99%; NTSC: 72%)  |
| Horizontal Sync      | 30 - 85kHz  |
| Viewable area W x H  | 478.7 x 260.3mm, 18.8 x 10.2"   |
| Pixel pitch          | 0.249mm   |
| Colour               | matte, white  |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                     |   |
|---------------------|---|
| Signal input        | HDMI x1<br>DisplayPort x1               |
| USB HUB             | x2 (v. 3.2 (Gen 1, 5Gbit; DC5V, 900mA)) |
| HDCP                | yes                                     |
| Headphone connector | yes                                     |

## 03 FEATURES

|                       |  |
|-----------------------|--|
| Blue light reducer    | yes  |
| Flicker free          | yes  |
| Adaptive Sync support | yes  |
| Extra                 | i-Style colour   |
| OSD languages         | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL   |
| Control buttons       | Joystick Controller/ Power Button : Forward (i-Style Colour/Blue Light Reducer), Backward (Select Input Source), Left (Eco), Right (Volume)  |
| User controls         | picture adjust (brightness, contrast, Eco, Blue Light Reducer, ACR, OD, MBR), colour settings (colour temp., user preset, i-Style colour), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, AMD FreeSync, RGB range, display information), input select (input source), audio settings (volume, mute) |
| Speakers              | 2 x 2W   |
| Convenience           | Kensington-lock™ prepared, DDC2B, Mac OSX  |

## 04 MECHANICAL

|                              |   |
|------------------------------|---|
| Display position adjustments | height, swivel, tilt, pivot (rotation both sides) |
| Height adjustment            | 150mm   |
| Rotation (PIVOT function)    | 90°   |
| Swivel stand                 | 90°; 45° left; 45° right                          |
| Tilt angle                   | 23° up; 5° down                                   |
| VESA mounting                | 100 x 100mm                                       |

Cable management system yes

## 05 ACCESSORIES INCLUDED

Cables power, USB, HDMI

Other quick start guide, safety guide

## 06 POWER MANAGEMENT

Power supply unit internal

Power supply AC 100 - 240V, 50/60Hz

Power usage 13W typical, 0.5W stand by, 0.3W off mode

## 07 SUSTAINABILITY

Regulations CE, TÜV-Bauart, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369) D

REACH SVHC above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D 493.5 x 326.5 (476.5) x 209.5mm

Box dimensions W x H x D 615 x 125 x 400mm

Weight (without box) 4.2kg

Weight (with box) 5.0kg

EAN code 4948570121946

---

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IYAMA CORPORATION. ALL RIGHTS RESERVED