# іїуата



## An Intel® i5 OPS slot PC with Windows® 11 IoT Enterprise and TPM 2.0 (Trusted Platform Module)

This mini OPS PC with Intel® Core<sup>™</sup> i5 inside turns your iiyama (interactive) large format display into a stand-alone solution. It comes equipped with a powerful Intel® processor with integrated Ultra HD graphics and a fast SSD drive. No hassle with cables and having to mount a PC at the back of the monitor or on a floor lift. The OPC51104BC-1 is also very quiet with a noise level below 34dB at 100% CPU load at 1meter distance. Simply slide in the iiyama OPS slot PC and get started right away.



#### DEVICE

| Туре                | OPS slot PC   |
|---------------------|---|
| CPU                 | Intel® Core™ i5-11300H, TPM 2.0 (Trusted Platform Module) |
| RAM                 | 8GB DDR4  |
| SSD                 | 256GB M.2   |
| Graphics            | Integrated Intel® Iris® Xe                                |
| Chipset             | Intel®  |
| Sound card          | Integrated High Definition Audio Stereo                   |
| Network             | 10/100/1000M Adapter                                      |
| WiFi                | 802.11 a/b/g/n/ac/ax (M.2 NVME)                           |
| Bluetooth           | 4 ~ 5.2   |
| Operating system    | Windows 11 IoT Enterprise                                 |
| LAN (RJ45)          | x1  |
| USB                 | 3.0 x2, 2.0 x2, 3.2 (Type C) x1                           |
| HDMI Out            | x1 (2.0)  |
| Headphone connector | yes   |
| Microphone In       | x1 (mic and headset combo)                                |

### 02 POWER MANAGEMENT

Power usage

95W typical, 0.5W stand by



| Product dimensions W x H x D | 180 x 30 x 119mm |
|------------------------------|------------------|
| Weight (without box)         | 1kg              |
| EAN code                     | 4948570033171    |



### 04 ENVIRONMENTAL CONDITIONS

| Operation temperature range | 0°C - 45°C    |
|-----------------------------|---------------|
| Operation humidity          | 5% - 95%      |
| Storage temperature range   | - 10°C - 50°C |
| Storage humidity            | 5% - 95%      |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED