



**Immerse yourself in the game with the curved GC2480HSU Red Eagle with 180Hz refresh rate**

The 1500R curved VA panel with 180Hz refresh rate and 0.5ms MPRT gives you an immersive viewing experience and guarantees superb image quality. Enhanced by the Black Tuner function, it provides detailed visibility in dark scenes, allowing you to spot every detail, even in low-light settings.



**CURVED DESIGN 1500R**

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.



**180Hz & 0.5ms MPRT**

With 180Hz refresh rate and 0.5ms MPRT response time the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.

## 01 DISPLAY CHARACTERISTICS

Diagonal	23.6", 59.8cm
Panel	VA
Curved	1500R
Native resolution	1920 x 1080 @180Hz (2.1 megapixel)
Aspect ratio	16:9
Panel brightness	300 cd/m <sup>2</sup>
Static contrast	3000:1
Advanced contrast	80M:1
Response time (MPRT)	0.5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn (sRGB: 96%, NTSC: 72%)
Horizontal Sync	30 - 200kHz
Viewable area W x H	521.4 x 293.3mm, 20.5 x 11.5"
Pixel pitch	0.271mm
Colour	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v. 2.0) DisplayPort x1 (v. 1.4)
USB HUB	x2 (v.2.0 (DC5V, 500mA))
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	yes
HDR	yes
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu (Up / Submenu, Down / Input Select, Left / ECO, Right / Volume)
User controls	picture adjust (contrast, brightness, OD, ACR, ECO, black tuner, colour saturation, motion blur red., AMD FreeSync), input source, audio settings (volume, mute audio), store user settings (user modes), colour settings (6-Axis, gamma, blue light reducer, colour temperature, user preset), image adjust (i-Style Colour, x-res technology, sharpness, RGB range, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED), information, recall
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

## 04 MECHANICAL

Display position adjustments	tilt
Tilt angle	22° up; 4° down
VESA mounting	100 x 100mm
Cable management system	yes

## 05 ACCESSORIES INCLUDED

**Cables** power (1.5m), USB (1.5m), HDMI (1.5m)

**Other** quick start guide, safety guide

## 06 POWER MANAGEMENT

**Power supply unit** internal

**Power supply** AC 100 - 240V, 50/60Hz

**Power usage** 21W typical, 0.5W stand by, 0.3W off mode

## 07 SUSTAINABILITY

**Regulations** CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA

**Energy efficiency class (Regulation (EU) 2017/1369)** E

**REACH SVHC** above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

**Product dimensions W x H x D** 535.5 x 394.5 x 202mm

**Box dimensions W x H x D** 622 x 408 x 171mm

**Weight (without box)** 3.8kg

**Weight (with box)** 6kg

**EAN code** 4948570124503

---

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED