



Enterprise-grade wireless presentation kit enabling native screen mirroring

Designed for large scale deployments and working through Miracast and Airplay protocol, the ScreenBeam 960 makes it easy to connect your Windows, Android or Apple device to the room display with a single click or swipe. Extended desktop frees up your device for other actions while presenting with both interactive touch displays and it is wireless touch supported.

Central Management System (CMS) software is included for remote management of receivers, providing enterprise-class security and manageability that IT departments need.

The kit contains the ScreenBeam 960A, a mounting bracket and a USB-power cable.

For more details, please click [HERE](#)

01 DEVICE

Operating system	Windows 10, Android 4.2 (and later), macOS 10 (and later), iOS 11 (and later)
LAN (RJ45)	x1
VGA In	x1
VGA Out	x1
HDMI Out	x1
USB-touch	x1
Headphone connector	yes
Audio	LCPM 2.0
Resolution	up to 1920x1080 @30Hz
Ethernet	RJ45 10/100 LAN
Features	touch support: 1 point, extended desktop with Windows OS
Language support	EN, DE, FR, PL, NL, RU, ES, IT, JP, CN, KO

02 TECHNICAL SPECIFICATION

WiFi standard Miracast P2P: 802.11ac; Infrastructure: 802.11a/b/g/n

03 POWER MANAGEMENT

Power supply unit external

Power usage	5W typical
--------------------	------------

04 SUSTAINABILITY

Regulations	CE, RoHS support, RED
--------------------	-----------------------

05 DIMENSIONS / WEIGHT

Product dimensions L x W x H	168 x 168 x 34.5mm
-------------------------------------	--------------------

EAN code	4948570032396
-----------------	---------------

06 ENVIRONMENTAL CONDITIONS

Operation temperature range	0°C - 40°C
------------------------------------	------------

Operation humidity	10% - 85%
---------------------------	-----------

Storage temperature range	- 0°C - 70°C
----------------------------------	--------------

Storage humidity	5% - 90%
-------------------------	----------

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED