

UNIFIED COMMUNICATIONS



INFORMATION

**Bluetooth Speakerphone for large meeting rooms**

The omnidirectional audio pickup from up to 5 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01L the perfect choice for large meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this sleek looking speaker can be paired with up to 3 devices at the same.



Omnidirectional

The UC SPK01L supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.



High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.



Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.



Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

TEHNICHESKIE-HARAKTERISTIKI

01 SPEAKER

Maximum sound pressure level	85dB
Distortion	≤4%
Signal to noise ratio	80dB
Frequency range	150Hz ~ 16kHz

02 MICROPHONE

Number of microphone arrays	x6
Voice pickup range	5m (radius)
Frequency range	150Hz ~ 8kHz

03 CONNECTIVITY & BUTTON OPERATIONS

USB Type C	x1 (Audio In/Out, Charge 5V/2A)
AUX	x1 (In/Out, 3.5mm, DaisyChain)
Bluetooth	4.2+EDR
Buttons	Power, Volume, Bluetooth, Mute, Answer/Hang up

04 ACCESSORIES & BATTERY

Bluetooth receiver	да
USB (type A to C) cable	да
Audio cable	yes
Battery capacity	7.4V/2200mAh
Charging	wired 5V/2A, wireless 5W
Battery life on a single charge	8 hours

05 СТАНДАРТЫ

Сертификаты CE, RoHS support, ErP, WEEE, REACH

06 РАЗМЕР / ВЕС

Вес (без упаковки)	0.4кг
EAN код	4948570033041

07 СОПУТСТВУЮЩАЯ ИНФОРМАЦИЯ

Сопутствующие [UC CAM120ULB-1](#), [UC CAM120UL-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC](#)

товары [CAM75FS-1, UC SPK01M](#)



Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселей. © IIYAMA CORPORATION. ALL RIGHTS RESERVED